

	FinCo Diesel B-0 Fuel for diesel engines for road vehicles and other combustion equipment	
Property	Limits	Test Method
Appearance	Clear and Bright	Visual inspection
Density at 15°C	820.0 - 845.0 kg/m ³	EN ISO 3675 / 12185
Sulfur content	Max. 10.0 mg/kg	EN ISO 20884 / 20846 / 13032
Cetane number	Min. 51.0	EN ISO 5165 EN 15195 / 16144
Cetane index	Min. 46.0	EN ISO 4264
Manganese content	Max. 2.0 mg/l	prEN 16576
Flash point	> 55°C	EN ISO 2719
Carbon residue (on 10% distillation residue)	Max. 0.30 % m/m	EN ISO 10370
Ash content	Max. 0.01 % m/m	EN ISO 6245
Viscosity at 40°C	2.00 - 4.50 mm ² /s	EN ISO 3104
Lubricity	Max. 460 µm	EN ISO 12156-1
Copper strip corrosion (3h at 50°C)	Class 1	EN ISO 2160
Total contamination	Max. 24 mg/kg	EN 12662
Oxidation stability	Max. 25 g/m ³	EN ISO 12205
Oxidation stability (not applicable if FAME content below 2 % v/v)	Min. 20.0 h	EN 15751
Water content	Max. 200 mg/kg	EN ISO 12937
Conductivity	Min. 50 pS/m	ASTM D2624
FAME content	Max. 0.5 % v/v	EN 14078
Polycyclic aromatic hydrocarbons	Max. 8 % m/m	EN 12916
Colour ASTM	Max. 2.0	ASTM D1500 / D6045
Distillation: Recovered at 250°C Recovered at 350°C 95% recovered at	< 65.0 % v/v Min. 85.0 % v/v Max. 360.0°C	EN ISO 3405 / 3924
CFPP: April/May/June/July/August/September March/October November/December/January/February	Max. -5°C Max. -11°C Max. -20°C	EN 116 / 16329
Cloud Point: April/May/June/July/August/September March/October November/December/January/February	Max. +4°C Max. 0°C Max. -5°C	EN 23015
WASA (not applicable if Cloud point equal or better than -7°C)	Min. 150 g/t	
Product code: 2303	Effective date: 10/10/2016	Revision number: 03